



March 3, 2011

MATERIAL SAFETY DATA SHEET

SECTION 1- MATERIAL IDENTIFICATION

Barnes TSX, TTSX, XPB, MZ, TMZ, T-EZ, TAC-X, TAC-TX, TAC-XP, LRX, SGS Bullets

SECTION II- INGREDIENTS

Chemical Name	CAS NO	Percent by wt.	Permissible Air Concentration (mg/m ³)	
			OSHA PEL	ACGIH TLV
COPPER	7440-50-8	98% Min	0.1 (Fume)	0.2 (Fume)

SECTION III - PHYSICAL DATA

Color:	Reddish
Melting Point (F):	1976-1981
Specific Gravity (H₂O=1):	8.89-8.94
Solubility in Water:	Negligible

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used):	Not Applicable
Extinguishing Media:	Dry Sand or Metal Extinguishing Powders
Special Fire Fighting Procedures:	Use NIOSH/MSHA approved self-contained breathing apparatus and Full protective clothing if involved in a fire.
Unusual Fire and Explosion Hazards:	Solid form can burn at minimum rate without flame (smolder). Do not use water on molten or smoldering metal. Grinding or other machining operations can produce fine particulate dust that may explode in the presence of a strong ignition source.

SECTION V – HEALTH HAZARD DATA

Specialty copper alloys are generally not considered hazardous in the form shipped (solid bars, billets, rods, wire, etc.) However, if your process involves grinding, melting, welding, cutting, or any other process that causes a release of dust or fume, hazardous levels of dust or fume of the constituents of these alloys could be generated. The following is a list of potential health effects for hazardous elements potentially contained in the alloys.

Primary Route(s) of Entry: Inhalation

Target Organs: Respiratory System

Acute Hazards: Elevated exposure to excessive concentrations of metal dust can cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Exposure to metal fumes can produce “metal fume fever”, which may include chills and fever, metallic taste in the mouth, dryness and irritation of the throat, cough, stomach pain, headache, nausea, vomiting, muscle and joint pain. The onset of symptoms may be delayed 4 to 12 hours, and could last from 12 to 48 hours.

Chronic Hazards: Copper dust and/or fumes may cause irritation of the eyes, skin and respiratory tract. Dry burning throat, headache, muscle aches, cough, nausea, chills, metallic taste, and skin and hair discoloration.

Medical Conditions Aggravated by Long-Term Exposure:

Persons suffering from chronic respiratory disorders may be adversely affected by exposure to metal fume and airborne particulate matter.

Emergency and First Aid Procedures:

Skin: Flush thoroughly with water.
Eyes: Flush with water, call physician.
Ingestion: Not a likely route of exposure. However, if ingested, seek medical attention.
Inhalation: For persons suspected of over-exposure to airborne fumes and particulates, remove person to fresh air. Seek medical attention promptly.

Carcinogenicity: Not identified as a carcinogen or potential carcinogen by NPT1, IARC2, or OSHA3.

- 1 National Toxicology Program
- 2 International Agency for Research on Cancer
- 3 Occupational Safety and Health Administration

SECTION VI – REACTIVITY DATA

Stability: Stable

Incompatibility (Material to avoid): Avoid contact with strong oxidizers. Avoid liberation of airborne dust that can be explosive.

Hazardous Decomposition Products: At temperatures above the melting point oxide fumes may be evolved.

Hazardous Polymerization: Will not occur.

SECTION VII – SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: A clean-up procedure that minimizes exposure is required. Vacuuming is preferred. Place material in closed containers. Do not use compressed air for cleaning. Use NIOSH approved respiratory protection if possibility of dust, and/or fume exposure exists.

Waste Disposal Method: Copper containing waste is normally collected to recover value. Should waste disposal be deemed necessary, follow all Federal, State, and Local disposal regulations.

SECTION VIII – SPECIAL PROTECTION INFORMATION

- Respiratory Protection:** If grinding, cutting, or machining of material generates airborne exposures above recommended limits, then a NIOSH approved respirator should be worn.
- Ventilation:** Exhaust dust, mist and/or fume away from the operator.
- Engineering Controls:** Use adequate ventilation to keep dust and/or fume concentrations below the occupational exposures limits shown in Section II.
- Eye Protection:** Safety glasses or a face shield should be worn, when appropriate.
- Gloves:** Protective gloves should be worn, when appropriate.

SECTION IX – SPECIAL PRECAUTIONS

Precautions to be taken in Handling and Storing:

Good housekeeping must be practiced during storage, transfer, handling, and use to avoid excess release of dust. Good personal hygiene procedures should be observed at all times after handling product.

DISCLAIMER OF LIABILITY

The information contained in this MSDS was obtained from sources believed to be reliable. HOWEVER, BARNES BULLETS EXTENDS NO WARRANTY OR GUARANTEES, EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS OF THE INFORMATION PRESENTED. It is the user's responsibility to determine the suitability of the information presented above, in assessing the hazards posed by the product under the conditions of use, and to take necessary measures to ensure compliance with all applicable laws and regulations.
