

Universe	Professional
Type	Verticality
Category	Pulleys
Subcategory	High-efficiency pulleys with swivel



SPIN L1

Openable even when attached to the anchor, the SPIN L1 pulley is designed for maximum simplicity in setting up hauling or load deviation systems, and tyroleans. The large diameter sheave mounted on sealed ball bearings gives it excellent efficiency. The swivel facilitates handling, allowing the pulley to be oriented under load, and direct connection of carabiners, ropes or slings.




Triple-action opening of the moving side plate is quick and easy, even with gloves.



The rope can be installed with the device connected to the anchor.



The red mark provides a visual warning when the moving side plate is unlocked.



The swivel accepts up to three carabiners and allows the use of ropes and slings to facilitate maneuvers.

Short Description Very high efficiency single pulley with swivel



Selling Points

- Designed for maximum simplicity in setting up hauling or load deviation systems and tyroleans for work at height, rescue and tree care:
 - triple-action opening of the moving side plate is quick and easy, even with gloves
 - the rope can be installed with the device connected to the anchor.
 - red mark provides a visual warning when the moving side plate is unlocked
 - special side plate design protects the rope path
- Optimal efficiency and easy handling:
 - large diameter sheave mounted on sealed ball bearings for excellent efficiency
 - swivel allows pulley to be oriented under load
 - swivel accepts up to three carabiners and allows the use of ropes and slings to facilitate maneuvers.

Specification

- Weight: 290g
- Certification(s): CE EN 12278, NFPA 1983 Pulley General Use, UIAA
- Material(s): aluminum, stainless steel, nylon
- Min. rope diameter: 7mm
- Max. rope diameter: 13mm
- Sheave type: sealed ball bearings
- Sheave diameter: 38mm
- Maximum working load: $4 \times 2 = 8\text{kN}$
- Breaking strength: 36kN
- Efficiency: 95%

Specifications by reference

Reference(s)	P001BA00	P001BA01
		
Color(s)	yellow	black
Made in	FR	FR
Guarantee	3 years	3 years
Inner pack count	1	1
Case quantity	12	12
EAN	3342540834927	3342540834842

Related product(s)

SPIN L2
 SPIN L1D
 PARALLEL 10.5 mm
 AXIS 11 mm
 VECTOR 12.5 mm
 RAY 11 mm
 BEAM 12.5 mm
 OK
 Am'D
 Bm'D
 OXAN
 VULCAN